

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/010602 A1

(51) International Patent Classification⁷: G02F 1/1339, 1/1341 (74) Agent: PARK, Young-Woo; 5F., Seil Building, #727-13, Yoksam-dong, Gangnam-gu, Seoul 135-921 (KR).

(21) International Application Number:
PCT/KR2004/001395

(22) International Filing Date: 11 June 2004 (11.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2003-0051560 25 July 2003 (25.07.2003) KR

(71) Applicant (for all designated States except US): SAM-SUNG ELECTRONICS CO., LTD. [KR/KR]; 416, Mae-tan-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 442-742 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SONG, Young-Goo [KR/KR]; 921-1201 Byuckjuckgol Samsung Apt., Young-tong-dong, Paldal-gu, Suwon-si, Gyeonggi-do 442-470 (KR). KONG, Hyang-Shik [KR/KR]; 644-304 Sinwon Apt., Yeongtong-dong, Paldal-gu, Suwon-si, Gyeonggi-do 442-729 (KR). KIM, Sung-Man [KR/KR]; 30-508 Jangmi Apt., Sincheon-dong, Songpa-gu, Seoul 138-240 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ARRAY SUBSTRATE FOR LCD



(57) Abstract: An array substrate (100a) includes a transparent substrate (304), a first insulation layer (306) and a pixel electrode (103). The transparent substrate (304) includes a display region (DR) that displays an image, a peripheral region (PR) having a driving circuit (101) for displaying an image through the display region, and a sealine region (SLR) that surrounds the display region (DR) to define the display region and the peripheral region (PR). The first insulation layer (306) is formed over the transparent substrate (304), and the first insulation layer (306) has an opening window (301) in the sealine region (SLR). The pixel electrode (103) is formed on the first insulation layer (306) of the display region (DR). The bonding between a color filter substrate (401) and an array substrate (100a) is improved. Furthermore, liquid crystal material is completely filled into between the color filter substrate and the array substrate.

WO 2005/010602 A1